

	FMS 2U	FMS 1U	F3400	F1000	F110
General					
Point-to-Point Protocol	•	•	•	•	
Accepts Expansion Cards	•	•			
Configuration Interface	HTML	HTML	HTML	HTML	HTML
Power	24VDC; 48VDC	24VDC; 48VDC	24VDC	24VDC	5VDC
Remote Firmware Upload	TFTP Upload/Serial Upload	TFTP Upload/Serial Upload	TFTP Upload/Serial Upload	TFTP Upload/Serial Upload	RLE Device Discovery Tool (UDP)
Alarm Notification & Escalation					
Web Browser Interface	•	•	•	•	•
Email	8 recipients	8 recipients	4 recipients	4 recipients	1 or more
SNMP Traps	•	•	•	•	•
Text, Numeric & Alphanumeric Pager (modem) Optional	•	•	•	•	
Status Updates & Information					
Web Browser	•	•	•	•	•
SNMP	•	•	•	•	•
Dial-up	•	•	optional	optional	
Modbus	Master/Slave	Master/Slave	Slave	Slave	Slave
BACnet	•	•	•	•	
Communications & Integrations					
Dry Contact Outputs	Up to 34	Up to 10	2	2	
4-20mA Inputs	Up to 56	Up to 20	4	4	
Thermistor			4	4	
Digital Dry Contact	Up to 104	Up to 32	24	4	8
Modbus/TCP	Master/Slave	Master/Slave	Slave	Slave	Slave
Modbus/RTU-485	Master/Slave	Master/Slave	Slave	Slave	
BACnet/IP	Master/Slave	Master/Slave	Slave	Slave	
Communication Ports					
Ethernet Ports	1	1	1	1	1
EIA-485 Ports	1	1	1	1	0
EIA-232 Ports	2	2	1	1	0